## RECOMMENDED LUBRICANTS AND FLUIDS - USA VEHICLES

| | | | AMBIENT TEMPERATURE °C | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| **COMPONENT** | **SPECIFICATION** | **VISCOSITY** | **-30** | **-20** | **-10** | **0** | **10** | **20** | **30** | **40** | **50** |
| Engine | Use oils to API service level SGSH or RES.22.OL.G4 or CCMC G4 | 5W/20 ) | | | | | | | | | |
| | | 5W/30 )<br>5W/40 ) | | | | | | | | | |
| | | 10W/30 | | | | | | | | | |
| | | 10W/40 )<br>10W/50 ) | | | | | | | | | |
| | | 15W/40 )<br>15W/50 ) | | | | | | | | | |
| | | 20W/40 )<br>20W/50 ) | | | | | | | | | |
| Automatic gearbox | ATF Dexron IID | | | | | | | | | | |
| Final drive units<br>Swivel pin housings | API or GL5<br>MIL - L - 2105 or<br>MIL - L - 2105B, C or D | 90 EP | | | | | | | | | |
| | | 80W EP | | | | | | | | | |
| Power steering | ATF Dexron IID | | | | | | | | | | |
| LT 230T transfer gearbox | API GL4 or GL5<br>MIL - L - 2105 or<br>MIL - L - 2105B | | | | | | | | | | |
| Brake reservoir | Brake fluid must have a minimum boiling point of 260°C (500˚F) and comply with FMVSS/116/DOT 4 | | | | | | | | | | |
| Lubrication nipples (hubs, ball joints, etc.) | NLGI-2 multipurpose lithium based grease | | | | | | | | | | |

**See table on page 3 for remaining vehicle components**



PDF Creator - PDF4Free v2.0 http://www.pdf4free.com