Engine V8

| 85 Nm | (63 lbf.ft) |
|---------|---|
| | (33 lbf.ft) |
| | (15 lbf.ft) |
| _ | (30 lbf.ft) |
| | (30 lbf.ft) |
| | (33 lbf.ft) |
| | , , |
| | (16 lbf.ft) |
| | (6 lbf.ft) |
| | (37 lbf.ft) |
| | (16 lbf.ft) |
| | (16 lbf.ft) |
| | (58 lbf.ft) |
| 6 Nm | (5 lbf.ft) |
| 6 Nm | (5 lbf.ft) |
| 85 Nm | (63 lbf.ft) |
| 45 Nm | (33 lbf.ft) |
| 85 Nm | 63 lbf.ft) |
| 10 Nm | (7 lbf.ft) |
| 13 Nm | (10 lbf.ft) |
| 8 Nm | (6 lbf.ft) |
| 22 Nm | (16 lbf.ft) |
| 15 Nm | (11 lbf.ft) |
| 22 Nm | (16 lbf.ft) |
| 15 Nm | (11 lbf.ft) |
| 270 Nm | (200 lbf.ft) |
| 22 Nm | (16 lbf.ft) |
| 40 Nm | (30 lbf.ft) |
| 50 Nm | (37 lbf.ft) |
| 50 Nm | (37 lbf.ft) |
| | (30 lbf.ft) |
| | (15 lbf.ft) |
| 80° | 80° |
| 13.5 Nm | (10 lbf.ft) |
| 45 Nm | (33 lbf.ft) |
| 72 Nm | (53 lbf.ft) |
| | (68 lbf.ft) |
| | (33 lbf.ft) |
| | (33 lbf.ft) |
| | (16 lbf.ft) |
| | (24 lbf.ft) |
| | 45 Nm 20 Nm 40 Nm 40 Nm 45 Nm 22 Nm 8 Nm 50 Nm 22 Nm 78 Nm 6 Nm 6 Nm 85 Nm 45 Nm 10 Nm 13 Nm 8 Nm 22 Nm 15 Nm 22 Nm 15 Nm 22 Nm 15 Nm 22 Nm 15 Nm 20 Nm 20 Nm 20 Nm 20 Nm 20 Nm 21 Nm 21 Nm 22 Nm 23 Nm 24 Nm 25 Nm 26 Nm 17 Nm 27 Nm 28 Nm 18 Nm 29 Nm 18 Nm 20 Nm 20 Nm 20 Nm 20 Nm 20 Nm 30 Nm 40 Nm 20 Nm 40 Nm |

^{*} New bolts must be fitted

⁺ Apply sealant, Part Number STC 50552 to threads