

Towing

TOWING WEIGHTS

Loading description	Suspension Type	Max. Trailer Weight	Tongue Weight	Max. Vehicle Weight
Trailer without brakes	All	1650 lb (750 kg)	330 lb (150 kg)	-
Trailer with brakes, off-road	All	2200 lb (1000 kg)	330 lb (150 kg)	-
Trailer with brakes, on-road with vehicle at Gross Vehicle Weight	Coil spring	4410 lb (2000 kg)	330 lb ⁽¹⁾ (150 kg)	710 lb (322 kg) (equivalent to driver, three passengers and 110 lb (50 kg) luggage)
	Self-levelling	4410 lb (2000 kg)	330 lb ⁽¹⁾ (150 kg)	900 lb (409 kg) (equivalent to driver and five passengers)
Maximum towing capacity on-road in low range ⁽²⁾	Coil spring	7700 lb (3500 kg)	550 lb (250 kg)	450 lb (204 kg) (equivalent to driver and 2 passengers)
	Self-levelling	7700 lb (3500 kg)	550 lb (250 kg)	600 lb (272 kg) (equivalent to driver and 3 passengers)
⁽¹⁾ It is permissible to increase the tongue weight to a maximum of 550 lb (250 kg), however the vehicle payload and rear axle loads must be reduced to keep within the GVW and maximum rear axle load. ⁽²⁾ All occupants should be seated in the first and second row seats.				

MAXIMUM ROOF RACK WEIGHT			
	On-road	Off-road	
Land Rover approved system	110 lb (50 kg)	66 lb (30 kg)	
NOTE: The weight of Land Rover approved roof bars and cross rail roof rack is allowed for before further weight calculations are made. However, if an alternative roof rack system is to be used, the weight of the system must be included as part of the load weight.			