



Specifications

Fluids

Item	Specification
* Anti-freeze	Havoline Extended Life Coolant (XLC) or any ethylene glycol based anti-freeze containing no methanol with only Organic Acid Technology (OAT) corrosion inhibitors
Anti-freeze concentration - Will provide frost protection to -40°C (-40°F)	50%
Specific gravity of coolant at 20°C (68°F), to protect against frost down to -40°C (-40°F)	1.068
Amount of anti-freeze to use for 50% concentration:	
Without rear passenger compartment heater	4.2 litres (6.7 pints) (4.0 US quarts)
With rear passenger compartment heater	5.6 litres (8.9 pints) (5.35 US quarts)



CAUTION: No other anti-freeze should be used with Havoline Extended Life Coolant.

Capacity

Item	Capacity
Without rear passenger compartment heater	8.4 litres (13.4 pints) (8.0 US quarts)
With rear passenger compartment heater	11.1 litres (17.8 pints) (10.7 US quarts)

General Specifications

Item	Specification
Cooling system type	Pressurised, thermostatically controlled with remote header tank
Radiator	Cross flow with integral transmission oil cooler
Expansion tank	Remote - fitted with a bleed screw and low coolant level sensor
Pressure cap rating	110 kPa (1.1 bar) (16 lbf/in ²)
Thermostat:	
Starts to open	88° C (190° F)
Fully open	95° C (203° F)
Cooling fan	Engine driven, viscous coupled with electronic control
Cooling fan diameter	470 mm (18.5 in)
Direction of rotation	Anti-clockwise
Coolant pump	Centrifugal flow impellor, belt driven from crankshaft

Torque Specifications

Description	Nm	lb-ft
Coolant pump bolts	10	7
Coolant pump pulley bolts	25	18

Power steering pipe clip bolt	10	7
Coolant expansion tank bolt	10	7
Vacuum pump bolts	10	7
Radiator bolts	25	18
A/C condenser bolt	6	4
Radiator access panel bolts	10	7
Cooling fan viscous coupling bolts	10	7
Cooling fan assembly	65	48