Mr./Mrs./Ms.:						Model:						İ	Reg. No.:											
nvoice/Job No.:					Odometer Reading:						V.I.N.:													
						,																		
Service type:	0	Α	0	В	0	Α	0	В	0	Α	0	В	0	Α	0	В	0	Α	0	В	0	Α	0	В
Months: ,000 miles:	3 4	6 8	9 12	12 16	15 20	18 24	21 28	24 32	27 36	30 40	33 44	36 48	39 52	42 56	45 60	48 64	51 68	54 72	57 76	60 80	63 84	66 88	69 92	72 96



DISCOVERY / LR4 (ALL MODELS ARDUOUS FROM 14MY)

Adjust/Lubricate/Replace - Labour cost included in scheduled time except items marked * Check - After the checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and material cost.

Chec	k - After the	checking procedure, cleaning, adjusting, repairing or replacing is subject to extra labour and mate	rial cost.	MAINTENANCE CHECK SHEET
	Oil	OIL SERVICE	MAIN SERVICE	(UNDER BONNET)
1. 2.		Renew engine oil and filter (Every 3 months / 4,000 mile) Inspect brake pads for wear, calipers for leaks and disks for condition (Every		ondition and check/top-up battery electrolyte level - low attery fitted - MENA markets only
3. 4. 5. 6.		3 months / 4,000 miles) Inspect road wheel speed sensor harness for damage (Every 3 months / 4,000 miles) Drain fuel sedimentor (Diesel)(Every 3 months / 4,000 miles) Adjust the electric park brake shoes (Every 3 months / 4,000 miles) Check the condition of the electric park brake system (Every 3 months / 4,000 miles)	36. Renew front and 80k Renew locking d 38. Renew automatic	
7. 8. 9.	A E	B MAIN SERVICE (VEHICLE INTERIOR) Check condition and security of seats and seatbelts Check operation of all lamps, horns and warning indicators Check operation of front/rear wipers and washers and condition of wiper blades Select the LOW range gears and drive the vehicle 3 to 4 vehicle lengths then re select HIGH range gears	40. Check for free pl 41. Check condition 42. Replace all flexib Check visually be electrical harnes 44. Check for fluid le 45. Check exhaust s	ay in all suspension and body mounting rubbers of all suspension, driveshafts and steering boots and gaiters ble brake hoses (<i>Every 6 years</i>)* rake servo hose, brake, fuel and PAS pipes, unions and ses for chafing, leaks and corrosion eaks system for leaks, security and damage
11.		Replace pollen filter MAIN SERVICE (VEHICLE EXTERIOR)	Check shock abs	od ball joint fixings and condition of ball joints and dust covers orbers/height sensors and harness assembly for leakage and
12. 13. 14. 15. 16. 17. 18. 19. 20. 21.		Check tyre pressures, condition and tread depth Remove road wheels Replace brake fluid (Every 2 years)* Renew fuel filter element (Diesel) Refit road wheels to opposite sides of the same axle (Use anti-seize compound on spigot bore) Not vehicles fitted with uni-directional tyres Visually check intercooler/radiator for external obstructions and fan blades for damage Renew the air suspension inlet filter Check operation of door checks, bonnet catch & fuel flap and lubricate door checks Apply lubricant to door seals - Russian and Nordic markets only Check condition of removable towbar	48.	
22. 23. 24. 25. 26. 27. 28. 29. 30. 31.	80	MAIN SERVICE (UNDER BONNET) Check anti-freeze specific gravity Renew coolant (Every 10 years)* Renew air cleaner element Check condition of ancillary driving belts Renew spark plugs (Every 6 years) Renew ancillary driving belts (Every 5 years) Renew supercharger driving belt (Every 4 years) Renew front and rear camshaft timing belts, tensioners and tensioner bolt (Diesel)(Every 5 years) Check/top-up brake and PAS fluid levels and screen washer reservoirs Check exterior of intercooler and remove debris using low pressure hose.	driving, road and climatic condition subject to stop/start operation, extr frequent towing of trailers. See reco Service check completed, cosmetic/co endorsed.	orrosion inspection check completed and service portfolio book
32.		Check/top-up battery electrolyte level - <i>low maintenance battery fitted</i>	Name: Sig	nature: Date:

JLR 19 03 10_1E 16/8/2013

WARNING: Two wheel roller tests must not be carried out. Four wheel roller tests must be limited to 5 km/hour (3 miles/hour).

IMPORTANT - OIL CHANGE DIESEL ENGINES

If the vehicle is operated on fuel with a high sulphur content (over 0.7) the oil change intervals must not exceed 6,500Km (4000 miles)

If the vehicle is operated on fuel with a moderate sulphur content (between 0.3 - 0.7) the oil change intervals must not exceed 13,000Km (8000 miles)

IT IS RECOMMENDED THAT:

Comments/Remedial Work

At 144,000 Km (90,000 miles) or every six years, whichever is the sooner, all hydraulic brake fluid hoses should be renewed

After 50 miles continuous use in severe off road conditions - wading, deep mud and abrasive grit/slurry - the electric park brake should be inspected, cleaned and adjusted, and the ancillary drive belt should be inspected and cleaned.

Air suspension vehicles used extensively in arduous/ off road conditions will require the compressor inlet filter to be replaced at more regular intervals.

When the vehicle is used in dusty or field conditions or deep wading, frequent attention to the air cleaner may be required.

When the vehicle is used in areas where fuel quality is poor, more frequent draining of the fuel filter/ sedimentor may be required.

For full details regarding the operations contained in this maintenance check sheet, please refer to the workshop manual.

GLOSSARY:

OIL SERVICE = The oil service is applicable to all vehicles. It is carried out at 3 month or 4,000 mile intervals, which ever occurs first.

MAIN SERVICE = The main service is applicable to all vehicles. It is carried out at 6 month or 8,000 mile intervals, whichever occurs first.

Main Service "A" is applicable at 6 months/8,000 miles, 18 months/24.00 miles, 30 months/40,000 miles 42 months/56,000 miles and so on.

Main Service "B" is applicable at 12 months/16,000 miles, 24 months/32,000 miles, 36 months/48,000 miles, 48 months/64,000 miles and so on. Some items do not need to be carried out at every main service and these items are identified by an indicator in the tick box e.g. 60k (This indicates that this item is only applicable every 60,000 miles)

NOTE: The service required should be at the time or distance stated, which ever occurs first.